

## **DOLLE SW26-3**





## 3-SECTION ATTIC LADDER.

Dolle SW23-6 is delivered with 20 mm insulated. It is a 3 section folding attic ladder which requires no headroom or storage space in the loft. The ladder is made of solid spruce and is delivered with non-slip treads for extra security. The hinges for the trapdoor are hidden which makes it easy to paint, varnish or clad the trapdoor. It has a specially developed height adjustment system. The SW23-6 is delivered with push/pull rod made of wood. It is fully assembled which makes it easy and and ready to install.



## **PRODUCTDATA**

| PRODUCTNAME                   | Dolle Hobby   |  |  |  |  |
|-------------------------------|---|--|--|--|--|
| TYPE                          | 3-section   |  |  |  |  |
| MATERIAL                      | wood  |  |  |  |  |
| PRODUCT-NO.                   | 26211 / 26217 / 26612 / 26712<br>Max. 281 cm                  |  |  |  |  |
| FLOORHEIGHT                   |   |  |  |  |  |
| HEIGHT WITH EXTRA TREADS      | Max. 350 cm<br>137 cm   |  |  |  |  |
| OUTLET IN CM                  |   |  |  |  |  |
| MAX. SWING CLEARANCE CM       | 162 cm  |  |  |  |  |
| NUMBER OF TREADS              | 12  |  |  |  |  |
| OPENING SIZE                  | 115x57 cm / 115x70 cm / 120x80 cm / 120x70 cm                 |  |  |  |  |
| NSULATION                     | 20 mm   |  |  |  |  |
| MATERIAL (CASING)             | spruce  |  |  |  |  |
| THICKNESS (CASING)            | 18 mm   |  |  |  |  |
| HEIGHT (CASING)               | 115 mm  |  |  |  |  |
| DUTSIDE CASING                | 112.5x54,6 cm / 112,5x67,6 cm / 117,5x57,6 cm / 117,5x67,6 cm |  |  |  |  |
| MATERIAL (TRAPDOOR)           | white HDF 2 x 3   |  |  |  |  |
| NSULATION (TRAPDOOR)          | 20 mm   |  |  |  |  |
| THICKNESS (TRAPDOOR)          | 26 mm   |  |  |  |  |
| THICKNESS (TREADS)            | 28 mm   |  |  |  |  |
| DEPTH (TREADS)                | 82 mm   |  |  |  |  |
| MIDTH (TREADS)                | 400 mm  |  |  |  |  |
| RISE (TREADS)                 | 250 cm  |  |  |  |  |
| MATERIAL (TREADS)             | spruce  |  |  |  |  |
| MATERIAL (STRING)             | spruce  |  |  |  |  |
| THICKNESS (STRING)            | 21 mm   |  |  |  |  |
| DEPTH (STRING)                | 84 mm   |  |  |  |  |
| MAX. HEIGHT CLOSED STAIR      | 32,8 cm   |  |  |  |  |
| MAX. HEIGHT ARM, CLOSED STAIR | 41,3 cm   |  |  |  |  |
| MAX, USERWEIGHT               | Tested by EN14975 up to 265 kg, work weight 150 kg            |  |  |  |  |
| J-VALUE                       | 1,33  |  |  |  |  |
| TEST                          | IFT Rosenheim EN12207 Class 4 @ 600 Pa                        |  |  |  |  |

## **MEASUREMENTS**

| Model<br>no | Casing<br>size (E) | Opening<br>size (D) | Floor-to-<br>ceiling<br>height<br>max. (A) | Casing<br>height | Number<br>of<br>treeds | Max.<br>landing<br>space<br>(B) | Max<br>swing<br>cleurance<br>(C) |
|-------------|--------------------|---------------------|--|------------------|------------------------|---------------------------------|----------------------------------|
| 26211       | 112,5 x 54,6       | 115 x 57            | 281 cm                                     | 11,5 cm          | 12                     | 137 cm                          | 162 cm                           |

G: 413 mm H: 67° - 71° J: 328 mm

