

# DOLLE SW26-3



## 3-SECTION ATTIC LADDER.

Dolle SW23-6 is delivered with 20 mm insulated. It is a 3 section folding attic ladder which requires no headroom or storage space in the loft. The ladder is made of solid spruce and is delivered with non-slip treads for extra security. The hinges for the trap-door are hidden which makes it easy to paint, varnish or clad the trapdoor. It has a specially developed height adjustment system. The SW23-6 is delivered with push/pull rod made of wood. It is fully assembled which makes it easy and ready to install.

## PRODUCTDATA

PRODUCTNAME	Dolle Hobby
TYPE	3-section
MATERIAL	wood
PRODUCT-NO	26712 / 26211 / 26217 / 26612
FLOORHEIGHT	Max. 283 cm
HEIGHT WITH EXTRA TREADS	Max. 350 cm
OUTLET IN CM	140 cm
MAX. SWING CLEARANCE CM	163 cm
NUMBER OF TREADS	12
OPENING SIZE	120x70 cm / 115x57 cm / 115x70 cm / 120x60 cm
INSULATION	20 mm
MATERIAL (CASING)	spruce
THICKNESS (CASING)	18 mm
HEIGHT (CASING)	115 mm
OUTSIDE CASING	117,5x67,6 cm / 112,5x54,6 cm / 112,5x67,6 cm / 117,5x57,6 cm
MATERIAL (TRAPDOOR)	white HDF 2 x 3
INSULATION (TRAPDOOR)	20 mm
THICKNESS (TRAPDOOR)	26 mm
THICKNESS (TREADS)	28 mm
DEPTH (TREADS)	82 mm
WIDTH (TREADS)	400 mm
RISE (TREADS)	250 cm
MATERIAL (TREADS)	spruce
MATERIAL (STRING)	spruce
THICKNESS (STRING)	21 mm
DEPTH (STRING)	84 mm
MAX. HEIGHT CLOSED STAIR	32,8 cm
MAX. HEIGHT ARM, CLOSED STAIR CM	41,3 cm
MAX. USERWEIGHT	Tested by EN14975 up to 265 kg, work weight 150 kg
U-VALUE	1,33
TEST	IFT Rosenheim EN12207 Class 4 @ 600 Pa

## MEASUREMENTS

Model no	Casing size (E)	Opening size (D)	Floor-to-ceiling height max. (A)	Casing height	Number of treads	Max. landing space (B)	Max. swing clearance (C)
26712	117,5 x 67,6	120 x 70	283 cm	11,5 cm	12	140 cm	163 cm

G: 413 mm  
H: 67° - 71°  
J: 328 mm

