



**K POST is a rapid setting concrete for securing metal, wood and concrete posts.**

**Ready to use. No mixing is required. Sets in 5 to 10 minutes. Finished job within hours.**



## Hassle Free Post Fixing

### Sets in 5 to 10 minutes




### 20kg showerproof bags



#### New showerproof, tough packaging benefits:

- ▶ Store on-site in all weathers
- ▶ No need to cover
- ▶ Stronger more durable 20kg sacks
- ▶ Reduces waste and damage resulting in cost saving
- ▶ Non-slip bag
- ▶ Cleaner and safer handling



|  |   |
|--|---|
|  <p>1</p> | <p>Dig a hole to the desired size, position the post in the hole then fill halfway with water.</p>                |
|  <p>2</p> | <p>Pour K POST evenly around the post, filling the hole.</p>  |
|  <p>3</p> | <p>Tap the setting surface to remove any air bubbles and cover with soil. K POST will set in 5 to 10 minutes.</p> |

| Post Size     | Hole size<br>(width x depth) | Number of K Post bags |
|---------------|------------------------------|-----------------------|
| 50 mm Round   | 150 mm X 450 mm              | 0.5                   |
|               | 200 mm X 300 mm              | 0.75                  |
|               | 200 mm X 600 mm              | 1.5                   |
| 75 mm Square  | 150 mm X 600 mm              | 0.5                   |
|               | 200 mm X 600 mm              | 1                     |
|               | 250 mm X 450 mm              | 1.5                   |
|               | 250 mm X 600 mm              | 2                     |
|               | 300 mm X 600 mm              | 3                     |
| 100 mm Square | 200 mm X 750 mm              | 1                     |
|               | 250 mm X 450 mm              | 1.5                   |
|               | 250 mm X 750 mm              | 2                     |
|               | 300 mm X 450 mm              | 2                     |
|               | 300 mm X 750 mm              | 3.5                   |

### Technical Support

Our technical team are available to provide specification and application advice.

For UK Support Tel: 028 2826 0766 For ROI Support Tel: 048 2826 0766


### Site Conditions

Do not use K POST if temperature drops below 5°C. Use only between 5°C to 30°C.

### Health & Safety

For full health and safety information please refer to the K Post Safety Data Sheet available to download from the literature library on our website. All equipment should be cleaned with water immediately after use. Residue must not enter drainage systems.

Visit [www.K-Rend.co.uk](http://www.K-Rend.co.uk) for more information.



### Kilwaughter Chemical Co Ltd

For UK Sales

9 Starbog Rd, Larne, Co. Antrim, N. Ireland, BT40 2TJ  
 Tel: 028 2826 0766 Fax: 028 2826 0136  
 Email: Sales@K-Rend.co.uk  
[www.K-Rend.co.uk](http://www.K-Rend.co.uk)



Certificate No. FM85394

For ROI Sales

Classis, Ovens, Co. Cork, Ireland  
 Tel: 021 4872733 Fax: 021 4871705  
 Email: Sales@K-Rend.co.uk  
[www.K-Rend.co.uk](http://www.K-Rend.co.uk)